



Wood Treated Right™



Wood Treated Right™



Wood Treated Right™

CONSUMER INFORMATION

HANDLING INSTRUCTIONS	RECOMMENDED HARDWARE
<ul style="list-style-type: none"> Do not burn pressure-treated wood. Wear a dust mask, goggles, and gloves when cutting or handling treated or untreated wood. After working with wood, wash exposed areas thoroughly. Wash work clothes separately from other household clothing before reuse. Pressure-treated wood should not be used where it may come into direct or indirect contact with drinking water, except for uses involving incidental contact such as freshwater docks and bridges. Do not use pressure-treated wood in circumstances where the preservative may become a component of food, animal feed, or beehives. Do not use pressure-treated wood for mulch. <p><i>For more details on handling ...</i> <i>...CCA-treated wood, see www.wolmanizedwood.com/hd/consumersafety.shtml</i> <i>...Copper azole-treated wood, see www.wolmanizedwood.com/use.shtml</i></p>	<ul style="list-style-type: none"> For Normal Outdoor Use: Hot-dipped galvanized fasteners (meeting ASTM A 153) and connectors (ASTM A 653 Class G185 sheet), or better, are recommended for protection against the effects of moisture often present where treated wood is used. For Extreme Conditions: For Permanent Wood Foundations, or where saltwater spray is present, use 304 or 316 stainless steel. For Dry, Protected Use: Galvanized fasteners are preferable, but the use of non-galvanized nails of sizes and types approved by the Model Code is acceptable when attaching joists, studs, or other framing to this sill plate, provided the wood will remain dry in service and protected from weather and water. Other exterior coated fasteners may be suitable. See manufacturers' specifications. Aluminum should not be used in direct contact with this wood. To do so would require an adequate physical barrier between the metal and wood.

CLAIMS DOCUMENT

GOODS DAMAGED IN TRANSIT – If goods arrive in poor order because of damage in transit, Buyer shall require truck driver to note same on shipping documents. Buyer shall then notify the sales representative assigned to it by Seller. Claims should be filed by Buyer with transit company, with five (5) days after products reach destination (or after destruction, if not delivered) and shipment must be held intact until settlement is made. **UNDER NO CIRCUMSTANCES SHOULD ESTIMATED DAMAGE BE DEDUCTED FROM THE INVOICE TOTAL UNLESS PRIOR APPROVAL HAS BEEN OBTAINED FROM SELLER'S SALES OFFICE.**

PRODUCT QUALITY CLAIMS – Buyer must file all quality claims with regard to the non-conformity of product to standard grades or other defect with Seller within five (5) days

after discovery of such non-conformity or defect, but, in any event, not later than thirty (30) after receipt of the material by Buyer. Buyer shall, by failure to give timely notice as specified above, waive any defects and void any warranty and the product sold hereunder shall be considered as accepted by the Buyer.

LIMITATION OF LIABILITY – Seller's liability resulting from non-conforming products is limited solely to the replacement of defective products or at the option of Seller, to repayment to the Buyer of the purchase price paid by Buyer upon the return to Seller of the non-conforming goods. In no event shall Seller be liable for any consequential, indirect, incidental, punitive, or special damages whatsoever, including, without limitation, damages for loss of business profits, business interruption and the like. The foregoing limitations and

disclaimers apply regardless of the causes or circumstances giving rise to the loss, damage, claim, or liability.

No other Warranties – Except as expressly provided in the invoice, Seller disclaims all other representations, warranties, and conditions, express, implied, statutory, or otherwise with respect to the products and services provided pursuant to the invoice, including but not limited to the implied representations, warranties, and conditions or merchantability and fitness for a particular purpose.

MOLD – Through our selection of mills, product storage, and rotation of inventory, we try to provide wood without mold. However, mold spores exist nearly everywhere and flourish wherever there is moisture. We cannot guarantee that the wood you receive will be mold-free.